



## TECHNICAL DATA SHEET

# KEIM DESIGN-FIXATIV

## 1. PRODUCT DESCRIPTION

---

Sol-silicate-based thinner and primer for KEIM Design-Lasur. KEIM Design-Fixativ is awarded with Cradle to Cradle Certified® Silver and C2C Certified Material Health Certificate™ Gold.

## 2. FIELD OF APPLICATION

---

KEIM Design-Fixativ is used for the pre-treatment of highly absorbent substrates and as a thinner for highly transparent glazes with KEIM Design-Lasur.

By applying two to three coats of KEIM Design-Lasur and KEIM Design-Fixativ, highly transparent glazes can be achieved, especially in the full-tone range. Attractive effects can also be achieved by using the same colour tone in different dilution levels.

## 3. PRODUCT PROPERTIES

---

- mineral matt
- realisation of individual transparency effects
- Cradle to Cradle Certified®-Certificate Silver
- C2C Certified Material Health Certificate™ Gold
- absolutely lightfast
- highly weather-resistant
- resistant to environmental impacts

### MATERIAL CHARACTERISTICS:

- Density: approx. 1,0 - 1.1 g/cm<sup>3</sup>
- pH value: approx. 11

### COLOUR SHADES:

milky

## 4. APPLICATION INSTRUCTIONS

---

### SUBSTRATE PREPARATION:

The substrate must be strong, dry, clean, sound and free from adhesion-reducing residues.

### APPLICATION CONDITIONS:

Ambient and substrate temperature during application and drying from  $\geq 5$  °C to  $\leq 30$  °C. Do not apply in direct sunlight or on sun-heated substrates. Protect surfaces from direct sun, wind and rain during and after application.

## TECHNICAL DATA SHEET – KEIM DESIGN-FIXATIV

---

### APPLICATION:

KEIM Design-Fixativ is particularly recommended as a thinner for highly transparent glazes and for glazes in the solid tone range. The prepared glaze must always be stirred well before and during work. Water or other materials must not be added. The glaze is applied with a suitable glaze brush (e.g. oval KEIM glaze brush) using the crosswise technique. When applying the glaze, it is important to work quickly and avoid build-up.

Note: The system components of the KEIM Design-Lasur system, Design-Lasur, Design-Base and Design-Fixativ can be mixed with each other in any ratio. KEIM Design-Base results in beautiful transparency with ideal processing consistency and layer thickness. KEIM Design-Fixativ allows highly transparent, colour-brilliant glazes with low layer thickness.

### CONSUMPTION:

approx. 0,05 l/m<sup>2</sup> for ready-to-use mixture of KEIM Design-Lasur and KEIM Design-Fixativ

These material consumption values are guide values for smooth substrates. Exact consumption values must be determined by means of test areas.

### CLEANING OF TOOLS:

Clean immediately with water.

## 5. PACKAGING

---

Container content	Unit of measure	Quantity on pallet	Type of container
20	l	24	jerry can
5	l	96	jerry can

## 6. STORAGE

---

max. storage time	Storage conditions
12 months	cool frost-free keep container tightly sealed. protected from heat and direct sun.

## 7. DISPOSAL

---

For disposal information refer to section 13 of the safety data sheet.

### EC WASTE CODE:

Waste code: 06 02 99

## 8. SAFETY INSTRUCTIONS

---

Please, refer to the Material Safety Data Sheet.

## 9. GENERAL INFORMATION

---

Cover surfaces not to be treated, especially glass, ceramics and natural stone. Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water.

Mixing with products not part of the system or other foreign additives is not permitted.

### 10. CERTIFICATES & QUALITY SEALS

---



The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



**KEIM MINERAL PAINTS LTD**

Santok Building / Deer Park Way, Donnington Wood / Telford / Shropshire TF2 7NA  
Tel. +44 1952 231 250 / Fax +44 1952 231 251  
[www.keim.com](http://www.keim.com) / [sales@keimpaints.co.uk](mailto:sales@keimpaints.co.uk)