



TECHNICAL DATA SHEET

KEIM WAX COATING

1. PRODUCT DESCRIPTION

KEIM Wax Coating is a two coat semi-permanent anti-graffiti system made from polymers and waterbased wax.

2. PRODUCT PROPERTIES

- easy to apply
- Easy to remove graffiti and recoat
- highly water vapour permable
- fire behaviour: non-flammable

MATERIAL CHARACTERISTICS:

- pH value: approx. 8,5

3. APPLICATION INSTRUCTIONS

4. PACKAGING

Container content	Unit of measure
-------------------	-----------------

5. STORAGE

max. storage time	Storage conditions
24 months	cool dry frost-free protect from moisture keep container tightly sealed.

6. DISPOSAL

For disposal information refer to section 13 of the safety data sheet.

Waste code: 08 01 12

7. SAFETY INSTRUCTIONS

Please, refer to the Material Safety Data Sheet.

8. GENERAL INFORMATION

Cover surfaces not to be treated, especially glass, ceramics and natural stone. Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water.

Mixing with products not part of the system or other foreign additives is not permitted.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIM MINERAL PAINTS LTD

Santok Building / Deer Park Way, Donnington Wood / Telford / Shropshire TF2 7NA
Tel. +44 1952 231 250 / Fax +44 1952 231 251
www.keim.com / sales@keimpaints.co.uk